



Immortal Dryback

Specification

Product name:	Immortal Dryback Plank
Floor type:	rigid core (SPC)
Structure:	3mm total thickness 0.7mm wear layer (28 mil)
Surface finish:	wood grain finish with Enhanced Ceramic Bead (ECB) coating for scratch and stain resistance
Bevel type:	micro-bevel
Installation:	glue down
Plank size:	48" x 7.25"
Packaging:	14 pieces / carton 34 sf / carton 50 cartons / pallet 20 pallets / container 41lbs / carton
Warranty:	Lifetime residential 30 year commercial

Performance Specification: Dryback

Classification	ASTM F1700-4	Class III Type B	
Dimensional Stability	ASTM F2199-09	≤0.166%	Surpasses requirements
Static Load Limit	ASTM F970-17	≤0.005" @ 250psi	Surpasses requirements
Residual Indentation	ASTM F1914-07	Average ≤8% Maximum ≤8%	Surpasses requirements Surpasses requirements
Static Coefficient of Friction	ASTM D 2047-4	N/A	>0.6 wet and dry
Resistance to Light	ASTM F1515-15	Average ΔE ≤8.0	Surpasses requirements
Resistance to Heat	ASTM F1514-03	Average ΔE ≤8.0	Surpasses requirements
Resistance to Chemicals	ASTM F925	No more than a slight change effect	Pass
Critical Radiant Flux	ASTM E648-17a	Class 1: ≥0.45 W/cm ²	Surpasses requirements
Smoke Density	ASTM E662-03	<450 flaming and Non-flaming	Surpasses requirements
Coefficient Wey and Dry	ASTM D 2047-04	≥0.60	Pass
Flexibility	ASTM F137	1" mandrel, no cracks/ breaks	Pass
Wear Resistance	ASTMD 3389-14	0.128	No minimum requirement
Phthalate content	CPSC-CH-C1001-09.3		None detected
Heavy Metals	EEN 71-3 Part3:1994		None detected
Certifications:	FloorScore, Greenguard Gold		

